

# 1834 PC PROGRAMMABLE



# TELEPHONE ENTRY SYSTEM



flush mount  
shown with trim ring -  
sold separately



surface mount



wall mount



**big characters**  
half inch LCD display



**stainless steel**  
plate and anti-vandal features  
protects all internal parts



**pc programmable**  
from your PC via modem  
or RS-232 interface



**large scroll**  
and call buttons

- Ideal for applications that do not require card access control or system expansion
- Visitors use the phone system to communicate with a resident who can grant or deny access via their own touch tone telephone
- PC programmable system allows programming from a pc via modem or RS-232 interface. DKS Remote Account Manager and Transaction Analysis software included
- Live Transactions allows you to view activity as it happens directly on your computer display
- Large A and Z scroll buttons and one touch CALL button makes system operation quick and easy
- Prewired for postal switch

FEATURES






## ACCESS CONTROL SOLUTIONS





# 1834 PC PROGRAMMABLE TELEPHONE ENTRY

The Model 1834 is an ideal telephone entry system that is suited for large applications that have a separate access control system, or in applications that require telephone entry access only. Visitors are easily identified by voice communication (a CCTV camera option provides visual ID as well\*) and can be granted or denied access directly from a touch-tone telephone.



## 1834 Surface

11.25" W x 13" H x 4.75" D  
285mm W x 330mm H x 120.6mm D

## 1834 Flush

12" W x 13.5" H x 2.5" D  
305mm W x 343mm H x 63.5mm D

## 1834 Wall

13.25" W x 15" H x 3.5" D  
336.5mm W x 381mm H x 88.9mm D

## 1834 Specs

### Communication

- True full duplex
- Hands free
- Optional handset (surface or flush mount only) (ADA compliant)

### Display

- Single line 20 character super-twist LCD - 1/2 inch characters

### Mounting Styles

- Surface mount - indoor or outdoor applications
- Flush mount - indoor or protected area applications requires flush mount kit
- Wall mount - indoor or outdoor applications

### Capacity

- Max 3000 phone numbers, 255 area codes
- 8000 event transaction memory
- 4 digit entry codes, capacity same as telephone number memory

### Door/gate control

- Two doors and/or gates

### Programming Methods

- Program via dial-up modem or RS-232 interface (requires second transformer) with included programming and transaction analysis software
- Other programming methods include system keypad and remotely from a touch tone telephone

### Advanced Features

- Full Duplex communication
- Remote Account Manager software
- Live Transactions (requires RS-232 connection)
- Database import/export capability using CSV file format
- Transaction buffer stores last 8000 events
- Programmable directory codes can be set from 1 to 4 digits in length
- 10 & 11 digit dialing capability
- Large A and Z scroll and CALL buttons
- Built in clock/calendar
- 8 hold open time zones
- Built in postal lock provision, EEPROM memory

### Optional

- Camera Ready: Optional B&W or Color CCTV camera\* can be added to the 1834
- \*may require additional CCTV equipment

### Operating Temp

- 10°F to 145°F
- 12°C to 62°C
- Optional heater kit available for colder climates

### Electrical Requirements

- 16 VAC, 20 VA System power (250ma) two transformers are sent with unit, second transformer for RS232 power
- U.L. listed power transformers provided
- Ringer equivalence: 0.0A Jack Type: RJ1C or W

### Safety Standards

- FCC (US) DUF6VT-12874-OTF
- DOC (CAN) 1736 4528 A
- Complies with UL 294
- ETL Listed

### Shipping Weight

- Approximately 15-20 lbs (6.8-9 kg)

### Warranty

- 2 year limited factory warranty

Distributed by:

## DOORKING®, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A. Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2005 All Rights Reserved. Product specifications may change without notice. Rev. 12/05

### MEMBER:

