

EAGLE-2000-APT

Specifications

Standard Features

2-Wire Master/Slave with Global Inputs
Open/Close Delay
One Pass (No Tailgate)
Motor Brake
24 VDC Output for MAG Lock
24 VAC Auxiliary Power Output
Partial Open
Stop-Reverse
Auto-Close Timer (1-60 sec.)

Gate Capacity & Operation

Rated Continuous Duty
12" Per Second Travel
Eagle-2000-APT
Maximum Gate: 2,000 lbs & 50 ft.
Eagle-2000-APT-1.5HP
Maximum Gate: 2,500 lbs & 50 ft.
Eagle-2000-APT-DM
Maximum Gate: 2,000 lbs & 50 ft.
High Traffic Application

Manual Release

Fail-Secure (FSC): Use crank to open
Eagle-2000-APT
Eagle-2000-APT-1.5HP
Eagle-2000-APT-DM

Mechanical

Chain: #40 Nickel Plated (20 ft.)
Gear Reducer: Size 60
Cover: All Weather/UV Resistant (HDPE)
Chassis: 1/4" Zinc Plated Steel to Resist Corrosion
Power Disconnect (1/2 HP)
Auxiliary 120 VAC Power Outlets (2)

Hardware

No-Weld Chain Brackets
UHMW Silent Idler Wheels
Audio Alarm
Pre-Wired Receiver Terminal
Hand Crank (FSC Models only)

Dimension

26" (h) x 18" (w) x 17" (d)

Shipping Weight

Eagle-2000-APT 150 lbs
Eagle-2000-APT-1.5HP 175 lbs
Eagle-2000-APT-DM 185 lbs

Power

Eagle-2000-APT
1 HP Continuous Duty AC
115 VAC @ 60 HZ 10.5 AMP
Eagle-2000-APT-1.5HP
Dual 3/4 HP Continuous Duty AC
Synchronized Operation
115 VAC @ 60 HZ 16.6 AMP
Eagle-2000-APT-DM
Dual 1 HP Continuous Duty AC
Motor 1 to Open/Motor 2 to Close
115 VAC @ 60 HZ 10.5 AMP

Operating Classification

Class I, II, III & IV

Compliance

UL 325 and UL 991
ETL Listed

Warranty

5-Year Limited (Commercial)
7-year Limited When Used in
Residential Application

Optional

Power II Battery Backup
Provides up to 40-80 Cycles

Installation Instructions

Easy to follow instructions. Available in Spanish.
Las instrucciones de la instalación disponibles
en Español.

Specifications Subject to Change

Model Number	Description	Gate Capacity
EAGLE-2000-APT	1 HP Heavy Duty Commercial Fail-Secure Slide Gate Operator. Continuous Operation.	Up to 50' & 2,000 lbs
EAGLE-2000-APT-1.5HP	Dual 3/4 HP Heavy Duty Commercial Fail-Secure Slide Gate Operator. Continuous Operation.	Up to 50' & 2,500 lbs
EAGLE-2000-APT-DM	Dual 1 HP Commercial Fail-Secure Slide Gate Operator For High Traffic Applications. Continuous Operation.	Up to 50' & 2,000 lbs



Heavy Duty Gearbox
Efficient & Quiet



Motor
Heavy Duty
Instant Reversing
Continuous Duty



Diamond Control Board
Easy to Use & State-of-the-art
Advanced Features Come Standard
Built-in Lightning & Surge Protection



Quiet Smooth Operation
UHMW Idler Wheels
Rubber Motor Mounts



Chain Kit
No-Weld Chain Brackets
#40 Nickel Plated Chain



Eagle-2000-APT Gate Operators for High Traffic Slide Gates to 50 ft. and 2,500 lbs

Apartment buildings, gated communities, industrial sites—anywhere there are big gates and a lot of traffic, Eagle-2000-APT is the best operator for the job.

The Eagle-APT series of operators is designed and built for the busiest sites delivering the rugged, durable power you need for these demanding applications.

Installation is made simple with the advanced features you most often need standard on every operator. Features like Stop-Reverse, allowing your transmitter to work like a 3-button station or Motor Brake for added control on downhill applications.

Master/Slave operation has never been easier. Just two wires provide full communication and Global Inputs between the master and slave operators. Connect any accessories to either the master or slave and the Diamond Control Board does the rest.

Install Eagle-2000-APT for reliable power.



UL325 UL991
compliant compliant
MADE IN THE USA

EAGLE ACCESS CONTROL SYSTEMS, INC.

13286 PAXTON ST.
PACOIMA, CA 91331

TOLL FREE (800) 708-8848 PHONE (818) 899-2777 FAX (818) 899-2666

WWW.EAGLEOPERATORS.COM EMAIL: INFO@EAGLEOPERATORS.COM

AVAILABLE AT:

Upswung LLC
P.O. Box 2713

Stateline, NV 89449-2713