

AEGIS 8000^{PLUS} SERIES

MULTI TENANT DEDICATED TELEPHONE ENTRY SYSTEM



- 250 tenants and 250 access codes.
- Programming:
 - Local via Keypad
 - Remote via dial-up modem
- Non-Volatile Memory
- Programming and Data Management with AeGIS Management Software
- Event recording with 600 events buffer
- 1x16 Liquid Crystal Display (LCD)
- Two relays • Support pause dialing from PBX
- Indoor or outdoor, surface and full-flush mount.
- Brushed Stainless Steel Faceplate *Warranty: 24 months*

SPECIFICATIONS

POWER INPUT: 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.

CURRENT CONSUMPTION: 500mA idle, 700mA operating.

OPERATING ENVIRONMENT: 32°F to 140°F. *Heater is required if the temperature is below 32°F.*

NIGHT LIGHT: Super Bright Light Emitting Diode (LED).

COMMUNICATION: 1200 Baud Modem

CONSTRUCTION: 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

MOUNTING: Surface and full-flush.

DIMENSIONS:

Surface 10-13/16" (H) x 8-5/8" (W) x 3-3/4" (D).

Full-flush 10-13/16" (H) x 8-3/8" (W) x 2-7/16" (D)

MOUNTING RING FULL-FLUSH (FFM7 is included):

Inside 11-1/8" (H) x 8-11/16" (W) x 2-5/8" (D)

Outside 14-5/16" (H) x 12-1/8" (W)

SHIPPING WEIGHT: 11-15 lb approximate.

see quick guide or manual for further specifications

ORDERING PART

Surface Mount

8250P

250 tenants 250 access codes

Full-flush Mount

8250FFP

250 tenants 250 access codes

ACCESSORIES

Radio Receiver and Transmitter

ARFR Radio Frequency Receiver
ARFT Radio Frequency Transmitter
ARFHT Radio Frequency Handheld Transmitter

Video Package

UVPC AeGIS Color Camera Package.
UVPB Video Balun for Twisted Pair video transmission

Pedestal Mounting Post, Adapter Plate and Mounting Ring

UPM1S Standard Single Arm (42"H, 5"x5" base)
UPM4S Standard Single Arm (47"H, 5"x5" base)
UPM1L Large Single Arm (47"H, 8"x8" base)
UPM6L Large Single Arm (64"H, 8"x8" base)
UPM8L Large Single Arm (84"H, 8"x8" base)
UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)
UPM5 Double Horizontal Arm (47"H, 8"x8" base)
UPMDB64 Single Arm Direct Buriel (64"H)
UPMDB72 Single Arm Direct Buriel (72"H)
UAP78 Adapter Plate AeGIS 8000P Series
UPM12E 12" Expansion Arm use for all UPM

Miscellaneous Accessories

AMDM 56K Desktop/Laptop Modem
FFM8 Full-flush mounting ring, *included w/ system*
USP1 AC and Telephone Surge Protector.
AHP5 Heater Pad with Thermostat.
UBAT1 12VDC 4.5 Ahr backup battery.
ARIGB8 Rough-in gang box.
UDIR Paper Directory with night light
8SHLD Sun Shield

PACH AND COMPANY
 Home of Telephone Access Control Systems

AEGIS QUANTUM

Phone: 1-888-678-7224

949-498-2951

www.pach-co.com