



# 1833 PC PROGRAMMABLE TELEPHONE ENTRY SYSTEM



**BEST SUITED FOR APPLICATIONS THAT DO NOT REQUIRE A DIRECTORY, OR WHERE A SEPARATE DIRECTORY ALREADY EXIST**



flush mount

surface mount

- Provides both resident and visitor access control into and within apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites
- Visitors use the phone system to communicate with a resident who can grant or deny access via their own touch-tone telephone
- Resident access control is provided by means of cards, digital PIN codes, or wireless transmitters
- PC programmable. Programming and Transaction Analysis software included
- 2 year limited factory warranty



**anti pass back**  
complete control into and out of secured areas



**modular**  
easy installation and service






**stainless steel**  
plate and anti-vandal features



**pc programmable**  
easy to use Remote Account Manager software included

# 1833 PC PROGRAMMABLE TELEPHONE ENTRY SYSTEM



## 1833 Surface

11.25" W x 13" H x 4.5" D  
(285mm W x 330mm H x 114.3mm D)

## 1833 Flush

12" W x 13.25" H x 3.25" D  
(305mm W x 336.5mm H x 82.5mm D)

1833	PHONE # MEMORY	ENTRY CODES	DEVICE CODES	RELAYS	DIRECTORY	ELEVATOR CONTROL	PROGRAMMING OPTIONS	OPTIONS	TRANSACTION BUFFER
<b>Surface Mount</b>	3000	1000 (4-digit)	8000	3 Built-in *	No	Yes	Computer or System Keypad		8000 Events
<b>Flush Mount</b>	3000	1000 (4-digit)	8000	3 Built-in *	No	Yes	Computer or System Keypad	Gold Plated Faceplate	8000 Events

\* Expands to 16 with tracker expansion boards.

## Technical Features

### Mechanical

Stainless steel faceplate  
Galvanized steel sub-plate  
Metal keypad  
Offset speaker holes for protection  
Hands free voice operation  
(Optional handset available on surface or flush mount only)  
Surface or Flush mounting styles  
Flush mount requires flush mounting kit  
Enclosures are rated NEMA 4x

### Connection Methods (for data transfer)

DK IM (Internet Modem) Server, Modem, RS-232, RS-422, Wireless, LAN, Internet (some of these methods will incur additional cost for hardware and/or service subscriptions)  
Database import/export capability using CSV file format

### Electrical

16 VAC (2 power transformer included)  
Full Duplex voice communication  
Stores up to 3000 phone numbers, 255 area codes  
Max 8000 Weigand device (card codes), 10 facility codes  
Transaction buffer stores last 8000 events  
Control 2 entry points, expandable to 16 with tracker expansion boards  
Programmable directory codes (1 to 4 digits)  
10 & 11 digit dialing capability  
31 security (permission) levels, 29 programmable with 4 time zones each, 32 holiday schedules  
Four-digit entry codes  
Built-in clock / calendar  
Hold open time zones (8)  
True Anti-Pass Back  
Elevator control option  
Live Transactions feature (requires TCP/IP internet connection or RS-232 connection)

### Miscellaneous

Environmental: 10°F to 145°F (-12°C to 62°C)  
ADA Compliant handset kit (P/N 1807-012) available on surface or flush mount only  
Camera Ready: Optional B&W or Color CCTV camera\*  
\*may require additional CCTV equipment  
Shipping weight approximately 15-20 Lbs (6.8-9 kg)



FCC (US) DUF6VT-12874-OT-T  
DOC (CAN) 1736 4528 A



Access Control Solutions since 1948

Distributed by:

MEMBER:



**DOORING, INC.**

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.  
Tel: 310-645-0023 FAX: 310-641-1586 www.dooring.com

© 2012 All Rights Reserved. Product specifications may change without notice.  
Rev. 9/12